

through-setting heavy duty anchors

Vorpa SAFETY THREADED NUT

Safety zincplated and A2 stainless steel threaded nuts

products group e technical data

SHEAR THREADED NUT

Anti-burglar nut with one-sided clamping system.

With a torque of about 19 Nm, the hexagonal head detaches without giving the possibility of tampering and disassembly of the object

To fix

- window and door frames
- gates
- railings
- iron bars
- traffic signals
- garden fittings



DTS P INOX A2
safety A2 stainless steel threaded nut with shear head and through hole



DTS PZ
safety zincplated threaded nut with shear head and through hole

Code	Description	Internal thread	Hexagon size	T _{inst} Nm indicative	Code	Description	Internal thread	Hexagon size	T _{inst} Nm indicative
58999	DTS P M 6/13	M6	13	15-25	59000Z	DTS PZ M 8/17	M8	17	15-25
59000	DTS P M 8/17	M8	17	30-40	59001Z	DTS PZ M 10/19	M10	19	30-40
59001	DTS P M 10/19	M10	19	75-85	59002Z	DTS PZ M 12/22	M12	22	75-85
59006	DTS P M 12/19	M12	19						

Reduced hexagonal size versionv

58996	DTS P M 8/13	M8	13	15-25	58996Z	DTS PZ M 8/13	M8	13	15-25
58997	DTS P M 10/17	M10	17	30-40	58976Z	DTS PZ M 10/17	M10	17	30-40



90840



90841



90842



90843



DTS INOX A2
safety A2 stainless steel M8 threaded nut with shear head



90840Z



90841Z



90842Z



90843Z

DTS Z
safety zincplated M8 threaded nut with shear head

Code	Description	Internal thread	Hexagon size	Ø	T _{inst} Nm indicative	Code	Description	Internal thread	Hexagon size	Ø	T _{inst} Nm indicative
90840	DTS SVASATO	M8	15		19	90840Z	DTS Z SVASATO	M8	15		19
90841	DTS	M8	13		19	90841Z	DTS Z	M8	13		19
90842	DTS 8/12	M8	15	12	19	90842Z	DTS Z 8/12	M8	15	12	19
90843	DTS 8/10	M8	15	10	19	90843Z	DTS Z 8/10	M8	15	10	19
4042	RONDELLA A2 10x20x2										
4049	RONDELLA A2 12x22x2,5										

THREADED NUT AF DRIVE

The special design of the permanent AF nut once brought to tightening, guarantees the inviolability of the mechanical anchor

To fix

- window and door frames
- gates
- railings
- iron bars
- traffic signals
- garden fittings



AF DRIVER SOCKET AND AF PERMANENT NUT

Code	Description	Nut	VHS AF anchor	A mm	B mm	Internal thread
72589	AF M8	art. 72590	art. 5717/5710/5712			
72592	AF M10	art. 72591				
72590	DADO AF M8			16,10	7,30	M8
72591	DADO AF M10			20,10	9,10	M10