

# MXP600

## FRONTLINE SAFETY, TODAY AND TOMORROW



Being on the front line is tough. Who knows what the day will bring, and what conditions your people will face? The right radio can make all the difference.

We've listened to what frontline workers want and built the MXP600 for them: a rugged and lightweight yet fully capable TETRA portable radio.

The MXP600 is easy to carry and easy to use. It has innovative audio technology so they can hear and be heard. It delivers best-in-class coverage with the option for Class 3 transmission power. Its rugged design copes with extreme environments, and its extended battery life outlasts a shift.

Bluetooth 5.0 and NFC enable rich collaboration, providing a leading-edge user experience today and ready for mission-critical communications tomorrow.

Over-The-Air-Programming and Over-The-Air Updates help keep your radios up to date and reduce expensive and time-consuming radio management chores to become lightning fast and cost effective.

The MXP600 is a radio that gives your frontline staff the confidence to focus and efficiently and effectively get the job done.

### KEY ATTRIBUTES

- Rugged and dependable
- Small and light
- Easy to carry and easy to wear
- Easy to use
- High receiver sensitivity
- Class 3 transmission power option
- Loud and clear audio
- Adaptive Multi-Microphone Beam-Forming Noise Suppression
- Adaptive Wind Noise Mitigation
- Automatic Howling Suppression
- Supports GPS, Beidou, Galileo and GLONASS
- Dedicated emergency button
- Long battery life
- Compact wired accessory connector
- Secure communications
- Large 2.4 inch colour screen
- Bluetooth 5.0
- Integrated NFC
- Hardware ready for High Definition (HD) voice
- Wi-Fi 2.4GHz and 5GHz
- TETRA Over-The-Air Programming
- Wi-Fi Over-The-Air Programming and firmware updates





## GENERAL SPECIFICATIONS

Dimensions	Height: 120mm Width: 54mm Depth: 25mm (with IMPRES2 1900mAh battery) 30mm (with IMPRES2 2900mAh or 3400mAh battery)
Weight	200g (with 1900mAh battery, without antenna) 212g (with 1900mAh battery and 60mm antenna)
Battery Options	1900mAh IMPRES2 battery 2900mAh IMPRES2 battery <sup>1</sup> 3400mAh IMPRES2 battery

## AUDIO

Audio Power at Rated	2W
Audio Distortion at Rated	<1%
Audio Power at Maximum	2.2W
Max Loudness	99Phon (standard profile) & 102Phon (loud profile)
Noise Suppression	Adaptive Multi-Microphone Beam-Forming
Number of Microphones	3 dedicated + 1 loudspeaker as mic
HD Voice	Capable (8kHz bandwidth)

## TETRA SERVICES

RF	
Frequency Bands	350-470 MHz
Transmitter RF Power	Class 3 (2.8W) Class 3L (1.8W) Class 4 (1W)
Adaptive Power Control	Per EN 300 392-2
Receiver Class	A and B
Receiver Static Sensitivity	-116dBm (guaranteed); -118dBm (typical)
Receiver Dynamic Sensitivity	-107dBm (guaranteed); -109dBm (typical)
DMO REPEATER	
DMO Repeater Mode Features and Functions	ETSI type 1A DMO repeater for channel efficient operation Repeats DMO voice and tone signalling on selected talkgroup Repeats SDS and status messaging on selected talkgroup Transmission of repeater presence signal Emergency Call (Pre-emptive Priority Call) Monitoring of and participation in calls whilst in repeater mode

DATA	
Short Data	Status messaging in TMO and DMO SDS messaging in TMO and DMO Supports concatenated SDS (1000 characters) Short data applications Callout (simple, full, E2EE) Access to SDS during an emergency call
Packet Data	Supports up to 4 slots packet data transmission
TETRA Network Protocol Type 1 (TNP1)	Simultaneous operation of packet data and short data services over a common Peripheral Equipment Interface (PEI)
AT Commands	Full set of ETSI and enhanced AT commands (including voice control)
AT Serial Multiplexer	Up to four virtual ports
VOICE	
Full Duplex Call	TMO: Private, PABX, PSTN, emergency
Half Duplex call	TMO: Private, group, emergency DMO: Private, group, emergency
Emergency Call Management (user customisable)	Tactical: Emergency group call to attached talkgroup Non-Tactical: Emergency group call to dedicated talkgroup Individual: Emergency call to pre-defined party (half/full duplex) Hot Mic: Allows user to talk without needing to press PTT button Emergency alert Emergency status message to dispatch console
Other Voice Functions	Inter-MNI Gateway Repeater PTT double push Pre-emptive priority calls
SECURITY	
Authentication	Infrastructure initiated and made mutual by radio terminal
Air Interface Encryption - Algorithms	TEA1 TEA2 TEA3
Protocols - Security Classes	Class 1 (Clear) Class 2 (SCK) Class 3 (DCK/CCK, OTAR-CCK, OTAR-SCK) Class 3G (GCK, OTAR-GCK)
End-to-End Encryption	AES128 or AES256 for voice and short data with OTAK supported through optional Hardware Security Module (HSM) SIM based encryption including BSI
Other Security Features	Temporary disable (stun) Permanent disable (either ETSI standard or customer restorable)

380-430

## CONNECTIVITY

Wi-Fi	
IEEE Standards Supported	802.11 a, b, g, n, ac
Wi-Fi Bands	2.4GHz and 5GHz
Authentication and Encryption	WPA WPA2 WPA2 Enterprise (EAP-TLS)
Security	TLS 1.2
BLUETOOTH	
Bluetooth Versions Supported	Bluetooth 5.0, 4.2, 4.1, 4.0, and 2.1 + EDR
Bluetooth Security	Supports AES encryption for both Bluetooth standard and low energy, complying to security service mode 4, level 4 with Secure Connections as recommended by NIST
Bluetooth Profiles	Headset Profile (HSP) Serial Port Profile (SPP) Generic Access Profile Generic Attributes Profile (GATT) including Heart Rate Profile, Battery Service Profile, Devices Info Profile
NFC	
Tag Type	ISO/IEC 15693
RFID	
Tag Type	866-868MHz or 902-928MHz
ANTENNA	
Connector	SMA
Impedance	50 Ω
Car kit	Compatible with external antenna

## LOCATION SERVICES

SATELLITE / OUTDOOR NAVIGATION SERVICE	
Constellations Supported	GPS plus one of: Galileo, GLONASS, and BDS (BeiDou), Satellite-Based Augmentation Systems (SBAS) including QZSS
GNSS Antenna	Internal antenna
GNSS Tracking Sensitivity	GPS: -163dBm (guaranteed) -164dBm (typical) BDS (BeiDou): -155dBm (guaranteed) -156dBm (typical) GLONASS: -157dBm (guaranteed) -160dBm (typical) Galileo: -155dBm (guaranteed) -157dBm (typical)
Horizontal Accuracy, 2D	1.2m (95% probable, -130dBm, >15 SVs Galileo and GPS)
TTF Cold Start	<60 sec (95% probable at -130dBm)
Protocols	ETSI LIP (short and long), Motorola Solutions LRRP
INDOOR NAVIGATION SERVICE	
BTLE Indoor Location	iBeacon™ / Bluetooth Low Energy Beacon
Protocols	ETSI LIP (extended)

## USER INTERFACE

Display	2.4" transfective display
	Easy to read modern user interface
	Backlight option
	Flip screen option
	Scalable text size option
	Customisable screensaver image
	Universal time display
	Configurable time out
	User configurable multiple display languages
Controls	Backlit keypad
	Dual function rotary knob
	3 configurable side buttons
	Configurable one touch keypad
Sensors	Accelerometer Ambient light
Talkgroup Management	User friendly, flexible, fast and efficient interface
Talkgroups	TMO folders: up to 256, TMO talkgroups: up to 10000 DMO folders: up to 128, DMO talkgroups: up to 2000
Favourite Talkgroup Folders	Up to 3
Scan Lists	40 lists of up to 20 groups
Country/Network Code List	Up to 100
Menu	Customisable menu list catering each user's need Menu shortcuts are available
Contacts Management	Rapid search to find the contact easily
Contacts	Up to 1000 contacts with 6 numbers per contact, (maximum 2000 unique numbers)
Multiple Dialling Methods	Dialling Direct, Scroll, Speed, One touch button/key
Call Alert	Vibrate alert and multiple ring tones
Message Management	Distinct folders for each message type for flexible message management
Text Message List	Up to 200 entries (short messages) At least 20 entries for outbox (long messages up to 1000 characters) At least 10 entries for inbox (long messages up to 1000 characters)
Status List	400 pre-defined messages Assignable to one touch buttons
Text Entry	Intelligent keypad text input
Covert Mode	Turns the device into stealth mode for undercover operation

# Select



## DEVICE MANAGEMENT SOLUTIONS

Customer Programming Software (CPS)	Supports CPS version 7.6 onwards
Integrated Terminal Management (iTM)	Supports iTM version 7.6 onwards
Over-The-Air Updates	Supports Over-The-Air-Programming (OTAP) for selected configuration (codeplug) information via TETRA network
	Supports Over-The-Air-Programming (OTAP) for configuration (codeplug) and Over-The-Air Updates (OTA Updates) for firmware via Wi-Fi

## ENVIRONMENTAL SPECIFICATIONS

Operating Temperature <sup>2</sup>	-30°C to +70°C
Storage Temperature	-40°C to +85°C
Humidity (Condensation & High), Temperature Change, Low and High Temperature	ETSI 300 019-1-7 class 7.3E
Shock (bumps & shock), drop (free fall & drop & topple) and vibration (random & sine)	ETSI 300-019 1-7 class 5M3
Dust and Water Ingress Protection	IP68 (2m, 2hr), IP67, IP66, IP65 per IEC 60529
Lab Accreditation	ISO/IEC 17025:2017

## US MILITARY STANDARD MATRIX

	MIL-STD810C		MIL-STD810D		MIL-STD 810E		MIL-STD 810F		MIL-STD 810G		MIL-STD 810H	
	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.
Low Pressure	500.1	I	500.2	II	500.3	II	500.4	II	500.6	II	500.6	II
High Temperature	501.1	I, II	501.2	I/A1, II/A1	501.3	I/A1, II/A1	501.4	I/Hot, II/Hot	501.6	I/A1, II/A1	501.7	I/A1, II/A1
Low Temperature	502.1	-	502.2	I, II	502.3	I, II	502.4	I, II	502.6	I, II	502.7	I, II
Temperature Shock	503.1	-	503.2	A1/C3	503.3	A1/C3	503.4	I	503.6	I-C	503.7	I-C
Solar Radiation	505.1	II	505.2	I/A1	505.3	I/A1	505.4	I/A1	505.6	I/A1	505.7	I/A1
Rain	506.1	I, II	506.2	I, II	506.3	I, II	506.4	I, III	506.6	I, III	506.6	I, III
Humidity	507.1	II	507.2	II	507.3	II	507.4	-	507.6	II/Aggravated	507.6	II/Aggravated
Salt Fog	509.1	I	509.2	I	509.3	I	509.4	-	509.6	-	509.7	-
Blowing Dust & Sand	510.1	I	510.2	I, II	510.3	I, II	510.4	I, II	510.6	I, II	510.7	I, II
Vibration	514.2	VIII/CatF, XI	514.3	I/Cat10, II/Cat3	514.4	I/Cat10, III/Cat3	514.5	I/Cat24, II/Cat5	514.7	I/Cat24, II/Cat5	514.8	I/Cat24, II/Cat5
Shock	516.2	I, II, V	516.3	I, IV, VI	516.4	I, IV, VI	516.5	I, IV, VI	516.7	I, IV, VI	516.8	I, IV, VI

## RECOMMENDED SERVICES

Services for TETRA radios

### Notes

Some features mentioned are optional, and some require additional software licences.

Feature availability may vary by country.

<sup>1</sup> Recommended for low temperature environments.

<sup>2</sup> Performance may be limited when operating at extreme temperatures.

Please check with your local Motorola Solutions representative for full details.



Sinora Srl

Via Carpegna 9, 47838 Riccione (RN)

marketing@sinora.it

Sinora Srl

Via Carpegna, 9 47837 Riccione RN

Riccione

Italia

marketing@sinora.it

+39.0541.694212